LC-POWER

LC7300 V2.3 - Silver Shield

PRO-LINE-Series

80 PLUS SILVER

ATX V2.3 / EPS 12V
Due to its current ATX V2.3 standard, the Silver Shield power supply works perfectly in modern as well as in older computer systems.

Dual/Quad Core Support
The power supply supports all modern DualCore, QuadCore and server systems.

PCI-Express x 1
Includes one PCI-Express 6 pin connector for a graphic card.

+12V Rail x 2
Silver Shield features two independent +12V rails (15 A/11 A) to provide stability and power for your system.

High Efficiency / 80 PLUS® SILVER certified
Modern technology decreases the standby mode power consumption and increases the efficiency of your power supply up to 89,20%.

Active PFC
Use active power factor correction (>0.99) to provide additional security to your system.

Advanced Security Circuitry
Over-Voltage Protection (OVP), Over-Current Protection (OCP), Over-Power Protection (OPP), Over-Temperature Protection (OTP), Under-Voltage Protection (UVP), Short-Circuit Protection (SCP)

120 mm Fan
Enjoy ultra silent work thanks to the high quality white 120 mm fan.

Connectors:	
1x 20+4 pin mainboard	40 cm
1x 4+4 pin mainboard 12V (8 pin EPS)	40 cm
1x PCI-Express 6 pin	45 cm
4x SATA	2x 40/2x 55 cm
3x PATA	1x 30/1x 45/1x 60 cm
1x FDD	75 cm

Barcode:	4260070122866
Mark of conformity:	TÜV, CE
Fan:	120 mm
PFC:	active
Weight (retail):	1,881 kg
Dimension:	86 x 150 x 140 mm
	(height x width x depth)

Power rating:	
+3,3V:	21 A
+5V:	15 A
max. combined:	103 W
+12V1:	15 A
+12V2:	11 A
max. combined:	300 W
max. combined:	300 W
max. peak load:	350 W